




BAPRO one
230V



Made in POLAND



UNIVERSAL
POWER
SUPPLY
230V/400Volts

Every year, we trust hundreds of customers buying BAPRO machines. This is sufficient proof that BAPRO machines are valued for the highest quality. The satisfaction and confidence of our customers to the brand and award appropriate for us BAPRO further motivation to work! We are proud of our products that contribute to the development of so many construction companies. Join the Group of our customers.



Plastering machine type **BAPRO one 230V** is the best mixing pump and sprayer for dry premixed materials. The big advantage of our machine is universal power supply 230 Volts or 400 Volts. Our machine characterized by unique in design, high performance work, simple operation, easy to transportation, optimal dimensions outer. Such attributes are the unique characteristic of the BAPRO brand. High performance series BAPRO one plastering machines powered by AC 230 Volt. Constructing we made sure that this machine was working fluid as for the individual 380 volt. It is known that the plastering machines during their work resists the mixing process. Our plastering machines is more than a 230 volt power supply! Our technical solution in the form of inverter combined with a very strong gearmotors provides the advantages of smooth operation. BAPRO plastering machines are the highest quality parts and ease of use. With infinitely variable speed we have optimal working conditions and very low running costs. So Do not wait and plastering machines BAPRO one 230V order today! See for yourself how good it is!



www.facebook.com/vogelsolidplastering
www.instagram.com/vogelsolidplastetring

JAKOŚĆ

QUALITY

गणु वत्ता

KVALITA

جودة

Якасць

質量

Calidad

Qualität

Qualità

Качество

ADVANTAGES !

- universal power supply 230 Volts or 400V
- required fuse B20
- variable speed control by the inverter
- variable pump rate
- ease of use and simple design
- high performance
- 5 - year warranty
- wide range of applications
- operational reliability
- long distance administration
- convenient transport
- low height of the hopper
- extensive hopper 130 liters
- compressor oil-free HANDY K2
- water and air fittings distributive includes a module of stainless steel
- reinforced geared motors NORD
- the opportunity to work with such devices
Pneumatic feeder mortar BAPRO 100/140
- high-quality components

For us always count details !

Water block made of stainless steel. Dual water filtration system through the use of filters, cleaning protects the components. No damage to the fittings and switches since they are protected.

Electrical control box: dust protection and excellent ease of maintenance. The best industrial automation system includes LEDs, enhanced aesthetics contactors and provides trouble-free control of the whole machine (high standard of work)

special gear motors NORD include mixed and pump gearmotor 5,5 kW and material feeder gearmotor 0,55 KW contains a special execution. Variable speed control by the inverter.

Water pump type 50M ensures the continuity of work to stabilize the water pressure to provide the best consistency of the mortar.



High performance component type K2 optimizes material maintenance free not contain oil and include pressure switch.

Maximum stability due to the robust frame structure. Three Elemental reinforced structure gives great freedom of maneuver in the plumb or level and easy to transport. We offer system of four wheels rotatable about 360 degrees to facilitate the movement

Very good equipment and high quality (aesthetics) provides safety and convenience continuous work. Long spray gun 100cm with special rotary coupling. Material hose and air hose with special rubber.



RECOMMENDED

Gypsum plasters

Gypsum liment plaster

Cement - lime plaster

Lining plasters (renderings)

Light plasters

Restoration plaster / renovating

Decorative plasters

Anhydrite floor screeds

Self levelling floor screed

Door frame grouting mortar

Bonding mortar

Spray plaster

Special refractory masses

Levelling plaster

Technical data

- Pumping : variable controlled by the inverter from 4 to 40 liter per minute
- Distance delivery : to 30 meter
- Power supply: 230 Volts / 50 Hz
- Drives : 2 three-phase motors 400V/ 50 Hz
- Gearmotor 5,5 kW 286 rpm controlled inverter speed control
- Gearmotor 0,55 kW 22 rpm
- Compressor 1040 W efficiency 250 l/min
- Dimensions L/W/H:1250/720/1530 mm
- Filing height : 90cm
- Total weight 260 kg

Contact

- ph: Grant Vogel- 0414439489
- email: grant@vogelsolidplastering.com.au
- web: vogelsolidplastering.com.au

